



# **UK Declaration of Conformity**

For the following equipment:

Product Name: LED Driver

Model Designation: HLG-WX-YZ

(W=100,120,150 or 185; X=H or blank; Y=12,15,20,24,30,36,42,48,54; Z=A,B,AB or blank)

The designated product(s) is(are) in conformity with the relevant legislation:

The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012: SI 2012 No. 3032

Implementing measure COMMISSION REGULATION(EC) No 2019/2020

The Ecodesign for Energy-Related Products and Energy Information (Amendment) (EU Exit) Regulations 2019

## Electrical Equipment (Safety) Regulations 2016:

BS EN 61347-1:2015

### **Electrical Compatibility Regulations 2016:**

## **EMI (Electro-Magnetic Interference)**

Conducted emission / Radiated emission

BS EN 55015:2013+A1:2015

| Harmonic current | BS EN 61000-3-2:2014 | Class C(≧50% load) |
|------------------|----------------------|--------------------|
| Voltage flicker  | BS EN 61000-3-3:2013 |                    |

#### **EMS (Electro-Magnetic Susceptibility)**

BS EN 61547:2009

| BO EN 010 11:2000         |                                      |                    |                                |
|---------------------------|--------------------------------------|--------------------|--------------------------------|
| ESD air                   | BS EN 61000-4-2:2009                 | Level 3            | 8KV                            |
| ESD contact               | BS EN 61000-4-2:2009                 | Level 2            | 4KV                            |
| RF field susceptibility   | BS EN 61000-4-3:2006+A1:2008+A2:2010 | Level 2            | 3V/m                           |
| EFT bursts                | BS EN 61000-4-4:2012                 | Level 2            | 1KV/5KHz                       |
| Surge susceptibility      | BS EN 61000-4-5:2014                 | Level 4            | 2KV/Line-Line                  |
| Surge susceptibility      | BS EN 61000-4-5:2014                 | Level 4            | 4KV/Line-Earth                 |
| Conducted susceptibility  | BS EN 61000-4-6:2014                 | Level 2            | 3V                             |
| Magnetic field immunity   | BS EN 61000-4-8:2010                 | Level 2            | 3A/m                           |
| Voltage dip, interruption | BS EN 61000-4-11:2004                | 30% dip 10 periods | 100% interruptions 0.5 periods |

Note:

Component power supply will be operated with a final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Regulations on the complete installation again. Tests above are only to be performed with LEDs.

For guidance on how to perform these EMC tests, please refer to TDF (Technical Documentation File).

To fulfill requirements of the latest ErP regulation for lighting fixtures, this LED power supply can only be used behind a switch without permanently connected to the mains.

This Declaration is effective from serial number GC1xxxxxxx

Person responsible for marking this declaration:

MEAN WELL Enterprises Co., Ltd.

(Manufacturer Name)

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan

(Manufacturer Address)

Aries Jian/ Director, Group R&D:

(Name / Position)

(Signature)

Alex Tsai/ Director, Product Strategy Center:

(Name / Position)

 Taiwan
 May. 27th, 2021

 (Place)
 (Date)