



## **Declaration of Conformity**

For	the	follo	wina	eani	pment
1 01	uic	10110	WILLIA	Cqui	PITICITE

Product Name: LED driver

Model Designation: HLG-480H-xy (x=24, 30, 36, 42, 48, 54; y=Blank, A, B, AB,D2,DX)

HLGP-480H-xy (x=24,30,36,42,48,54; y=Blank,A,B,AB)

is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards

were applied:

RoHS Directive (2011/65/EU), (EU)2015/863

Energy-Related Products Directive (2009/125/EC)
Implementing measure COMMISSION REGULATION(EC) No 2019/2020

Low Voltage Directive (2014/35/EU):

ENEC certificate No: 35-103722

## **Electromagnetic Compatibility Directive (2014/30/EU):**

## **EMI (Electro-Magnetic Interference)**

Conducted emission / Radiated emission

EN IEC 55015:2019+A11:2020

Harmonic current	EN IEC 61000-3-2:2019	Class C(≧40% load)				
Voltage flicker	EN 61000-3-3:2013+A1:2019					
EMS (Electro-Magnetic S	MS (Electro-Magnetic Susceptibility)					

EMS (Electro-Magnetic S	Susceptibility)		
EN 61547:2009			
ESD air	EN 61000-4-2:2009	Level 4	15KV
ESD contact	EN 61000-4-2:2009	Level 4	8KV
RF field susceptibility	EN 61000-4-3:2006/A2:2010	Level 2	3V/m
EFT bursts	EN 61000-4-4:2012	Level 2	1KV/5KHz
Surge susceptibility	EN 61000-4-5:2014/A1:2017	Level 4	2KV/Line-Line
Surge susceptibility	EN 61000-4-5:2014/A1:2017	Level 4	4KV/Line-Earth
Conducted susceptibility	EN 61000-4-6:2014	Level 2	3V
Magnetic field immunity	EN 61000-4-8:2010	Level 2	3A/m
Voltage dip_interruption	EN IEC 61000-4-11:2020 <5% residual voltage for 250 cvo	al voltage for 0.5 cycles ,70% les	6 residual voltage for 25

Voltage dip, interruption cycles, <5% residual voltage for 250 cycles

Component power supply will be operated with a final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.

Tests above are only to be performed with intended loads, i.e. either with LEDs or resistive load.

For guidance on how to perform these EMC tests, please refer to TDF (Technical Documentation File).

To fulfill requirements of the latest ErP regulation for lighting fixtures, this LED power supply can only be used behind a switch without permanently connected to the mains.

This Declaration is effective from serial number TC1xxxxxxx

Person responsible for marking this declaration:

MEAN WELL Enterprises Co., Ltd.

(Manufacturer Name)

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan

(Manufacturer Address)

(Name / Position)

Aries Jian/Director, Group R & D:

Alex Tsai/ Director, Product Strategy Center:

(Signature) (Name / Position)

 Taiwan
 Aug. 12th, 2021

 (Place)
 (Date)

Version: 4

(Signature)