



# **UK Declaration of Conformity**

| Cartha  | fal | 10,41,000 | ~~!!nm~n+ | ٠ |
|---------|-----|-----------|-----------|---|
| roi ine | 101 | lowing    | equipment | ٠ |

Product Name: Medical Type Switching Power Supply

Model Designation: MSP-450-x (x=3.3,5,7.5,12,15,24,36,48)

The designated product(s) is(are) in conformity with the relevant legislation:

The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic

Equipment Regulations 2012: SI 2012 No. 3032

Medical Devices Regulations 2002 (SI 2002 No 618, as amended) (UK MDR 2002)

BS EN 60601-1-2:2015+A1:2021

#### **EMI (Electro-Magnetic Interference)**

Conducted emission / Radiated emission

|                  | BS EN 55011:2016+A2:2021     | Class B |
|------------------|------------------------------|---------|
| Harmonic current | BS EN IEC 61000-3-2:2019     |         |
| Voltage flicker  | BS EN 61000-3-3:2013+A1:2019 |         |

## **EMS (Electro-Magnetic Susceptibility)**

|                           | ,, ,                         |                        |   |
|---------------------------|------------------------------|------------------------|---|
| ESD air                   | BS EN 61000-4-2:2009         | Level 4                | 15KV  |
| ESD contact               | BS EN 61000-4-2:2009         | Level 4                | 8KV   |
| RF field susceptibility   | BS EN IEC 61000-4-3:2020     | Level 3                | 10V/m(80MHz-2.7GHz)                             |
| RF field susceptibility   | BS EN IEC 61000-4-3:2020     | Table 9                | 9~28V/m (385MHz~5.78GHz)                        |
| EFT bursts                | BS EN 61000-4-4:2012         | Level 3                | 2KV/100KHz                                      |
| Surge susceptibility      | BS EN 61000-4-5:2014+A1:2017 | Level 4                | 2KV/Line-Line                                   |
| Surge susceptibility      | BS EN 61000-4-5:2014+A1:2017 | Level 4                | 4KV/Line-Earth                                  |
| Conducted susceptibility  | BS EN 61000-4-6:2014         | Level 3                | 10V   |
| Magnetic field immunity   | BS EN 61000-4-8:2010         | Level 4                | 30A/m   |
| Voltage dip, interruption | BS EN IEC 61000-4-11:2020    | 100% dip 1 periods 30% | 6 dip 25 periods 100% interruptions 250 periods |

### Note:

A component power supply with load will be installed into final equipment which consists of an electronically shielded metal enclosure. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-gualify EMC Directive on the complete installation again.

The EMC tests mentioned above are performed using a well defined metal plate to simulate said metal enclosure. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies".(as available on <a href="http://www.meanwell.com">http://www.meanwell.com</a>)".

The product under declaration is just a unit without medical function. Complete MDR should only be verified when it is used together with particular medical device(s).

This Declaration is effective from serial number SC4xxxxxxx

# Person responsible for marking this declaration:

MEAN WELL Enterprises Co., Ltd.

(Manufacturer Name)

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan

(Manufacturer Address)

Aries Jian/ Director, Group R&D:

(Name / Position)

Signature) ies

Alex Tsai/ Director, Product Strategy Center:

(Name / Position)

on)

(Signature)

Taiwan (Place) Feb. 16th, 2024

(Date)