



# Test Report : N7815

---

1A Non-Isolated DC-DC Switching Regulator

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

## ■ SAFETY TEST

## ■ RELIABILITY TEST

Environment Test

**■ DESIGN VERIFY TEST**
**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT
1	VOLTAGE ACCURACY	-3.0% ~ +3.0% (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	-0.23%
2	RIPPLE & NOISE	100 mVp-p (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	20 mV
3	LINE REGULATION	-0.3% ~ +0.3% (Max)	I/P:20VDC~36VDC O/P:FULL LOAD Ta:25°C	-0.10% ~ -0.07%
4	LOAD REGULATION	-0.4% ~ +0.4% (Max)	I/P:24VDC O/P:0% LOAD~FULL LOAD Ta:25°C	-0.04% ~ +0.05%

**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	20 VDC ~36 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	8.35 VDC ~36 VDC
2	EFFICIENCY	96% (Typ)	I/P:24VDC O/P:FULL LOAD Ta:25°C	96.37%
3	DC CURRENT	785 mA / FULL LOAD (Max) 10 mA / NO LOAD (Max)	I/P:24VDC O/P:NO / FULL LOAD Ta:25°C	781 mA / FULL LOAD 9.25 mA / NO LOAD

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT
1	SHORT PROTECTION	CONTINUOUS	I/P:36VDC O/P:FULL LOAD Ta:25°C	HICCUP MODE AUTO-RECOVER
2	OVER LOAD PROTECTION	200% ~ 300% (Typ)	I/P:24VDC O/P:TESTING Ta:25°C	243% HICCUP MODE AUTO-RECOVER

**RELIABILITY TEST**
**ENVIRONMENT TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT										
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:FULL LOAD Ta=71°C 3. HIGH AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:70% LOAD Ta=85°C												
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> <th>3</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>74.9°C</td> <td>120.9°C</td> <td>116.5°C</td> </tr> </tbody> </table>			NO	Position	1	2	3	1	CASE	74.9°C	120.9°C	116.5°C
NO	Position	1	2	3										
1	CASE	74.9°C	120.9°C	116.5°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:24VDC O/P: FULL LOAD Ta= -40°C	TEST : OK										

**OTHER**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 0.52838 M.T.B.F : 1,892,591.64HRS		

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG