



## **Declaration of conformity**

| For the |  |  |  |
|---------|--|--|--|
|         |  |  |  |
|         |  |  |  |
|         |  |  |  |

Product Name: LED Driver

Model Designation: NPF-xy-z (x=40, 60; y= D or blank; z=12,15, 20, 24, 30, 36, 42, 48, 54)

PWM-x-y (x=40, 60; y= 12, 24, 36, 48)

is herewith confirmed to comply with the requirements set out in the Council Directive, the following standards were applied:

RoHS Directive (2011/65/EU), (EU)2015/863

Energy-Related Products Directive (2009/125/EC)
Implementing measure COMMISSION REGULATION(EC) No 2019/2020

Low Voltage Directive (2014/35/EU):

EN 61347-1:2015 EN 61347-2-13:2014+A1:2017 ENEC certificate No: 35-116654

## Electromagnetic Compatibility Directive (2014/30/EU):

## **EMI (Electro-Magnetic Interference)**

Conducted emission / Radiated emission

|                         | EN IEC 55015:2019+A11:2020 |         |                    |
|-------------------------|----------------------------|---------|--------------------|
| Harmonic current        | EN IEC 61000-3-2: 2019     |         | Class C(≧60% load) |
| Voltage flicker         | EN 61000-3-3: 2013+A1:2019 |         |                    |
| EMS (Electro-Magnetic S | Susceptibility)            |         |                    |
| EN 61547:2009           |                            |         |                    |
| ESD air                 | EN 61000-4-2:2009          | Level 3 | 8KV                |
| ESD contact             | EN 61000-4-2:2009          | Level 2 | 4KV                |
| RF field susceptibility | EN IEC 61000-4-3:2020      | Level 2 | 3V/m               |
| EFT bursts              | EN 61000-4-4:2012          | Level 2 | 1KV/5KHz           |
| Surge susceptibility    | EN 61000-4-5:2014+A1:2017  | Level 4 | 2KV/Line-Line      |

| Magnetic field immunity   | EN 61000-4-8:2010   | Level 2 3A/m                                      |  |  |
|---------------------------|---|---|--|--|
|                           | EN IEC 61000-4-11:2020                                      | <5% residual voltage for 0.5 cycles ,70% residual |  |  |
| Voltage dip, interruption | voltage for 25 cycles , <5% residual voltage for 250 cycles |   |  |  |

## Note:

Component power supply will be operated with a final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.

Tests above are only to be performed with LEDs.

For guidance on how to perform these EMC tests, please refer to TDF (Technical Documentation File).

EN 61000-4-6:2014

This Declaration is effective from serial number GC1xxxxxxx

Person responsible for marking this declaration:

MEAN WELL Enterprises Co., Ltd.

(Manufacturer Name)

Conducted susceptibility

No.28, Wuquan 3rd Rd., Wugu Dist., New Taipei City 24891, Taiwan

(Manufacturer Address)

Aries Jian/ Director, Group R&D:

(Name / Position)

(Signature)

Alex Tsai/Director, Product Strategy Center:

Level 2

3V

(Name / Position)

(Signature)

Taiwan

Dec. 28th, 2021

(Place) (Date)