



# Test Report : SKMW30W8-03

---

30W 1"x1" Package 8:1 Ultra-Wide Input DC-DC Regulated Converter

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

## ■ SAFETY TEST

Safety test

## ■ RELIABILITY TEST

Environment Test

Other

**DESIGN VERIFY TEST**
**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-1.5% ~ +1.5%	I/P:48VDC O/P:FULL LOAD Ta:25°C	-1.90%	P
2	RIPPLE & NOISE	150 mVp-p	I/P:48VDC O/P:FULL LOAD Ta:25°C	68mV	P
3	LINE REGULATION	-0.5% ~ +0.5%	I/P:9VDC~75VDC O/P:FULL LOAD Ta:25°C	+0.25% ~ +0.06%	P
4	LOAD REGULATION	-0.5% ~ +0.5%	I/P:48VDC O/P:0% LOAD~FULL LOAD Ta:25°C	-0.46% ~ +0.49%	P

**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	85%	I/P:48VDC O/P:FULL LOAD Ta:25°C	85.70%	P
2	DC CURRENT	567mA / FULL LOAD 10mA / NO LOAD	I/P:48VDC O/P:NO / FULL LOAD Ta:25°C	548mA / FULL LOAD 5.98mA / NO LOAD	P

**PROTECTION FUNCTION TEST**

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	SHORT PROTECTION	CONTINUOUS	I/P:75VDC O/P:FULL LOAD Ta:25°C	CONTINUOUS, AUTOMATIC RECOVERY	P
2	OVER LOAD PROTECTION	110~200%	I/P:48VDC O/P:TESTING Ta:25°C	173.0% HICCUP MODE AUTO-RECOVER	P
3	CASE TEMPERATURE	+105°C max	I/P:48VDC O/P:TESTING Ta: TESTING	OK AUTOMATIC RECOVERY	P
4	OVER VOLTAGE PROTECTION	YES	I/P: 48VDC O/P: MIN LOAD Ta:25°C	PROTECTION TYPE : CLAMP BY ZENER DIODE	P
5	UNDER VOLTAGE LOCKOUT	START-UP 8.5V(Type) SHUTDOWN OLTAAGE 8.0V(Type)	I/P:TESTING O/P:FULL LOAD Ta:25°C	8.45 VDC 8.02 VDC	P

## CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	POWER ON : R.C. ~ -VIN >3.5~75VDC OR OPEN CIRCUIT POWER OFF : R.C. ~ -VIN <1VDC OR SHORT	I/P:48VDC O/P:100% LOAD Ta:25°C	POWER ON : R.C>1.44VDC OR OPEN POWER OFF : R.C.<1.41VDC OR SHORT	P
2	TRIM CONTROL	+10%~ -10% (Typ) Trim ~ +Vout Trim DOWN Trim ~ -Vout Trim UP Using 1M ohm VR	I/P:48VDC O/P:FULL LOAD Ta:25°C	Trim DOWN -9.6% Trim UP +10.4%	P

## SAFETY TEST

### SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>1000MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>1000MΩ NO DAMAGE	P

## RELIABILITY TEST

### ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT										
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:48VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 4HRS I/P:48VDC O/P:FULL LOAD Ta=50°C 3. HIGH AMBIENT BURN-IN : 4HRS I/P:48VDC O/P:70% LOAD Ta=65°C												
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> <th>3</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>55.8°C</td> <td>80.8°C</td> <td>88.3°C</td> </tr> </tbody> </table>			NO	Position	1	2	3	1	CASE	55.8°C	80.8°C	88.3°C
NO	Position	1	2	3										
1	CASE	55.8°C	80.8°C	88.3°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:48VDC O/P: FULL LOAD Ta= -40°C	TEST : OK										

## OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 0.615384 M.T.B.F : >1,625KHRS		

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG